



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



Emissions Monitoring in the Refinery Industries



Refinery Industry Emissions Monitoring

Crude Oil Heaters / Furnaces / Incinerators

Procal 2000 measures products of combustion and can accommodate changes caused by variations in the make up of off-gas fuel. The heated probe option is especially suited to this application as it efficiently deals with variations in process temperature. It also keeps the probe hot, ensuring immediate availability when the plant is restarted after an outage.

Typical Ranges:

SO ₂	0 – 2,000 ppm
NO	0 – 500 ppm
NO ₂	0 – 500 ppm
H ₂ O	0 – 15%



Power Plant – Electricity and Steam

Procal 2000 is the ideal, field-proven, device to monitor emissions from refinery power plants. The instrument is compliant with international standards therefore meeting the stringent requirements of Environment Agencies.

Typical Ranges:

SO ₂	0 – 200ppm
NO	0 – 500ppm
NO ₂	0 – 500ppm
H ₂ O	0 – 15%



Klaus Unit

Capable of reliably measuring the high concentrations of SO₂ found in a Klaus Unit, Procal 2000 can be offered with special corrosion-resistant materials such as Hastelloy 'C'. Procal 2000 is the only in-situ IR analyser on the market that is available with optional ATEX / IEC approval for use in ZONE 1 Hazardous Areas such as those found in many refinery applications.

Typical Ranges:

SO ₂	0 – 2%
H ₂ O	0 – 2 %



Catalyst Cracker Vent

This is an application for which the Procal 2000 analyser is well suited. The sintered filter assembly can function well even in cases where dust levels in the sample are high.

Typical Ranges:

SO ₂ Normal	0-700ppm
SO ₂ Plant Upset	0-14000ppm
NO	0-300ppm
NO ₂	0-250ppm



Comprehensive ATEX / IEC approved solutions

In addition to ATEX / IEC approved analysers, Procal offer a range of accessories suitable for installation in hazardous areas. For example, steam-heated probes and bypasses can be used to ensure that the sample temperature is maintained above the acid dew point.



Parker Procal

Hydraulic Filter Division Europe
Emission Monitoring Centre
5 Maxwell Road Peterborough PE2 7HU
United Kingdom
Tel: +44 (0)1733 232495
Fax: +44 (0)1733 235255
Email: procal@parker.com
Web: www.procal.com www.parker.com

Distributed by: